



TYPE SPS SUPER STARCO™

The Super Starco™ bucket is the result of intensive research to achieve the maximum individual bucket capacity, while still maintaining the perfect fill and discharge characteristics of the original Starco bucket over a wide speed range.

- > Versatile bucket, available in many sizes
- > Increased Volume, with the same discharge characteristics as the Starco™ bucket
- > Less buckets required per metre
- > Less bolts and punching required
- > Reduced cost for belt & bucket installation

HDP / NYLON / POLYURETHANE

Agricultural & Industrial



No.	A (mm)	B (mm)	C (mm)	D (mm)	T (mm)	HDP (kg)	Nylon (kg)	PU (kg)	Capacity (Litres)		No.	Holes			Available Options	Max. Pcs/Mtr
									Z2 (total)	Z3 (water)		Ø E (mm)	F (mm)	G (mm)		
SPS80-80	90	85	63	43	4	0.08	0.09	0.10	0.24	0.20	2	9.0	43	18	R	15.00
SPS100-90	110	100	67	44	5	0.11	0.13	0.15	0.39	0.32	2	9.0	50	20	R	14.00
SPS120-100	129	110	80	55	5	0.15	0.18	0.20	0.61	0.48	2	9.0	67	25	R	12.00
SPS130-120	135	120	85	57	5	0.19	0.23	0.25	0.72	0.54	2	9.0	70	25	R	11.00
SPS140-120	145	120	90	62	5	0.18	0.22	0.24	0.81	0.62	2	8.5	70	25	R	10.80
SPS130-130	146	130	90	60	5	0.21	0.25	0.28	0.88	0.68	2	9.0	70	25	R	10.80
SPS160-140	172	152	113	78	6	0.34	0.40	0.45	1.55	1.25	2	9.0	100	30	R	8.60
SPS180-140	187	150	112	77	6	0.30	0.36	0.40	1.79	1.42	2	9.0	100	30	R	8.60
SPS200-150	205	150	112	75	6	0.35	0.42	0.46	1.89	1.39	2	9.0	100	32	R	8.60
SPS300-150	305	152	115	80	7	0.65	0.77	0.86	2.92	2.28	4	9.0	51-102-51	32	N-R	8.50
SPS200-160	210	158	115	79	7	0.39	0.46	0.51	2.20	1.77	2	9.0	100	32	R	8.50
SPS230-170	240	175	138	93	7	0.61	0.73	0.81	3.09	2.42	2	11.0	120	36	R	7.00
SPS240-165	250	170	132	93	7	0.54	0.64	0.71	3.12	2.42	2	11.0	120	35	R	7.40
SPS280-165	293	170	132	95	7	0.67	0.79	0.88	3.75	3.06	3	11.0	80	36	N	7.40

TYPE SPS SUPER STARCO™



No.	A (mm)	B (mm)	C (mm)	D (mm)	T (mm)	HDP (kg)	Nylon (kg)	PU (kg)	Capacity (Litres)		No.	Holes			Available Options	Max. Pcs/Mtr
									Z2 (total)	Z3 (water)		Ø E (mm)	F (mm)	G (mm)		
SPS280-170	282	175	138	97	7	0.67	0.80	0.88	3.77	2.96	3	11.0	80	37	R	7.00
SPS280-180	290	185	140	97	7	0.84	1.00	1.11	4.21	3.34	3	11.0	80	36	N	7.00
SPS300-180	316	185	140	97	8	0.85	1.01	1.12	4.69	3.79	3	11.0	100	36	N-F	7.00
SPS330-180	347	185	140	97	8	0.90	1.07	1.19	5.30	4.10	3	11.0	110	38	N-F	7.00
SPS350-180	367	186	140	97	9	1.12	1.33	1.48	5.35	4.27	3	11.0	120	38	N-F	7.00
SPS300-215	318	220	168	117	9	1.18	1.40	1.56	6.66	5.38	3	11.0	100	50	R	5.88
SPS330-215	343	220	168	117	9	1.30	1.55	1.72	7.20	5.86	3	11.0	120	50	N-R-F	5.88
SPS350-215	368	220	168	117	9	1.38	1.64	1.82	7.75	6.20	3	11.0	120	50	R	5.88
SPS370-215	390	220	168	117	9	1.45	1.72	1.91	8.45	6.48	4	11.0	90	50	N-R-F	5.88
SPS400-215	420	220	168	117	9	1.54	1.83	2.03	9.10	7.29	4	11.0	100	50	R	5.88
SPS450-215	470	220	165	115	9	1.56	1.86	2.06	9.95	7.80	5	11.0	90	50	N-R	5.88
SPS500-215	525	220	168	117	9	1.84	2.19	2.43	11.60	9.00	5	11.0	100	50	N-R-F	5.88

N = no holes / F = flat holes / R = recessed holes / RO = recess on the outside only
Wear band size: 3.0mm on 1 or 3 sides on request / * Slotted holes to fit alternate hole centres

Free Engineering Design Service - contact 4B or visit: www.go4b.com